

# Roots® Blower

## 36 URAI DSL

Part Number – T3038002x\*

Repair Kit w/o Gears: 651050RK

\*Replace “x” with shaft location (i.e., L=Left, T=Top, etc.)

- Shaft Configurations available: Left, Right, Top, Bottom
- Detachable steel mounting feet
- Rigid one-piece cast iron casing
- Connections in standard pipe sizes
- Straight, precision machined two-lobe impellers
- Splash oil lubricated gear and drive ends
- Carburized and ground alloy steel spur timing gears
- Anti-Friction gears
- Ground steel shafts
- Center Timed for rotation in either direction

### Also Available in:

- URAI
- URAI-J (Whispair)
- URAI-G (Gas)
- URAI-J-DSL

### Direct Drop-in Replacement for:

**Sutorbilt Model 3LP**

**Tuthill Model 3006\***

*\*Model size 3006 is supplied with 7/8" diameter drive shaft. When replacing with a Roots model you will need to adjust your drive components to accommodate the 3/4" drive shaft of the Roots blower.*

### Quick Specs

Flow Range	to 330 CFM
Max ΔPressure	7 PSI
Max ΔVacuum	15" Hg
Maximum RPM	3600
Minimum RPM	1090
Max ΔT	225°F
Connection Size	2.5" FPT
Shaft Dia.	0.75"
Min Sheave Dia.	5"
Drive End Lubrication	Oil
Gear End Lubrication	Oil
Oil Sump Gear End Horiz Config	10.5 oz
Oil Sump Gear End Vert Config	8.5 oz
Oil Sump Drive End Horiz Config	6.5 oz
Oil Sump Drive End Vert Config	4 oz
Bare Unit Weight	78 lbs
Shipping Weight	82 lbs
Shipping Container	Box
Box Size (L x W x H)	17" x 16" x 12"
Can Ship via	UPS Insured



## Roots Authorized

Representative  
Distributor

Packager

Repair Center

**816-207-0090**

Sound Enclosures  
Custom Fabrication

Blower Packages

Valves, Gauges & Sensors

Spool Pieces

Blower Parts

Oil and Grease

Silencers & Filters

Filter Elements

Air Handling Equipment

Screw Conveyors



5155 E Front Street  
Kansas City MO 64120  
info@jlcomponents.com  
816-207-0090