

Roots® Blower



832 Tri-RAM

Part Number – RH-205421x*

Repair Kit: RK800TRI00T (Call if unit is bottom shaft)

*Part number changes dependent on shaft location, discharge, and optional feet and adapters.

- Tri-lobe impellers for less vibration and minimal downstream pulse
- The head plates and rigid, one-piece cylinders are cast iron, and the drive-end and gear covers are cast iron
- WHISPAIR™ discharge design combined with tri-lobe impellers for quieter operation than conventional tri-lobe blowers
- Carburized and ground alloy steel timing gears for long life and consistent performance
- Cylindrical roller bearings for longer bearing life
- Piston ring seals for less air leakage
- Splash lubrication from oil sumps with sight glasses on each end for easy maintenance
- Detachable feet and drive shaft extension to adapt to horizontal or vertical configuration



Quick Specs

Flow Range	to 5399 CFM
Max ΔPressure	12 PSI
Max ΔVacuum	16" Hg
Maximum RPM	2670
Minimum RPM	475
Max ΔT	230°F
Connection Size	12" FLG or Rect
Shaft Dia.	2.755"/70mm
Min Sheave Dia.	12"
Drive End Lubrication	Oil
Gear End Lubrication	Oil
Oil Sump Horiz Config	376 oz
Oil Sump Vert Config	224 oz
Bare Unit Weight	2870 lbs
Container	Wood Skid
Skid Size (L x W x H)	54" x 32" x 28"
Shipping Weight on Skid	~2920 lbs
Recommended to Ship Via	Truck

Roots Authorized

Representative

Distributor

Packager

Repair Center

816-207-0090

Sound Enclosures

Custom Fabrication

Blower Packages

Valves, Gauges & Sensors

Spool Pieces

Blower Parts

Oil and Grease

Silencers & Filters

Filter Elements

Air Handling Equipment

Screw Conveyors

